

**MONOPOLE
NO. 1**
—
**CLAY
ROOF TILE**

AWAITING IMAGE

AWAITING IMAGE



TECHNICAL SERVICES:

Quantity Estimating:

For a detailed roof material quantity schedule, please send us your project drawings in PDF format.

Fixing Specification:

BS 5534 states that all interlocking tiles must be mechanically fixed. Use Edilians' roof tile fixing calculation service to ensure your roof is designed & installed in accordance with BS 5534.

Roof Specifications:

We can write a detailed specification for your project based on the information you supply. This will include a wind load calculation to ensure your roof is designed & installed in accordance with BS 5534.

CAD Detailing:

CAD details are available on our website and also from FASTRACKCAD www.fastrackcad.com for all our tiles & for all common roof details. For bespoke details, please contact our Technical Support team.

MANUFACTURING STANDARDS

Edilians tiles fully comply with the requirements of BS EN 1304; the European Standard for clay tiles & fittings & are manufactured under a Quality Management system certified to comply with ISO 9001.

ENVIRONMENTAL STANDARDS

All Edilians manufacturing sites are certified to Environmental Management System ISO 14001. In addition, Edilians complies with BES 6001: Responsible Sourcing. Edilians has a corporate policy for sustainable development, with environmental & social implementation key components of its overall performance. Strict standards are set for its manufacturing plants for emission, water & waste management. Responsible environmental management is important to Edilians by restoration of the landscape. Creating valuable wildlife habitats and recreation of heathland areas & forestry.

INSTALLATION

All tiles, fittings & accessories should be installed in accordance with the recommendations given in BS 5534: the British Standard Code of practice for slating & tiling. Sitework should be carried out in accordance with BS 8000-6: the British Standard for workmanship on building sites. Contact Edilians Technical Support for projects where the rafter length exceeds 6 metres.

CONTROL OF CONDENSATION

Adequate provision to prevent potentially harmful roof space condensation must be provided. In general, this can be achieved by following the guidance in BS 5250, through a combination of measures, including low & high-level ventilation, vapour permeable or air & vapour underlays & well-sealed ceilings as defined in BS 9250. Contact Edilians technical Support for further information.




30 YEAR GUARANTEE

Edilians clay roof tiles are covered by a comprehensive 30-year guarantee of durability provided that they have been installed in accordance with BS 5534 & BS 8000-6.



Edilians is continually innovating and improving its products and services. Therefore, we reserve the right to change product specifications without notice. Please contact us for the latest information or visit www.edilians.co.uk

EDILIANS ROOF TILES
Site Industriel De Quincieux
BP47 - Z1 - 69650 Quincieux - France
Tel: 0161 928 4572
Fax: 0161 929 8513
Email: enquiries@rooftilesedilians.com




edilians.co.uk

08/2019

MONOPOLE NO. 1

CLAY ROOF TILE

Traditional Roman Interlocking Clay Roof Tiles
Ref. 306



Uniclass	L5211
CI/SFB	(47) Ng2

edilians.co.uk

OUR SOLUTIONS



MONOPOLE NO. 1

CLAY ROOF TILE

Traditional Roman Interlocking Clay Roof Tiles

The Edilians Huguenot MONOPOLE NO 1 is a traditional single roman interlocking clay roof tile produced at Wardrecques in the north of France.

Economical and versatile, the small modular size of the MONOPOLE makes it ideal for a wide range of refurbishment and new build projects, offering cost savings over all concrete plain tiles.

FEATURES

A hugely popular tile, economical and versatile, available in seven eye-catching colours and a pre-mixed blend.

COLOURS



NUANCE (131)

NATURAL RED (076)

RUSTIC RED (006)



BURNT RED (034)

GLOSS BLACK (047)

WEATHERED (109)



VIEUX NORD (119)
(PRE-MIXED BLEND)

To overcome any minor shade variations inherent in the production of natural clay products, we recommend that tiles are mixed from at least 3 pallets on site. The colours shown here are only as accurate as allowed for by the printing process. Product samples are available on request.

Technical data

Quantity per pallet:
600 tiles

Coverage at
241mm gauge:
22.0 tiles per m²

Batten gauge*
241mm

Overall length:
297mm

Overall width:
215mm

Cover width:
189mm

Headlap:
56mm

Weight per tile:
2.0kg

Weight per m²:
44.0kg

Minimum roof pitch*:
25.0°

Batten coverage per m²:
4.15m

Batten sizes:
38 x 25mm for rafter
centres up to 450mm

50 x 25mm for rafter
centres up to 600mm

Tile nail:
50 x 3.35mm
aluminium clout head

* Always check each batch of tiles delivered to site to determine the actual gauge, which may vary slightly due to drying and firing shrinkage during the manufacturing process

RUSTIC RED (006)


EDILIANS MONOPOLE NO. 1 ACCESSORIES AND FITTINGS

An extensive range of accessories covering all roofing needs


Verge




Cloaked verge




Half round interlocking ridge




Ornamental ridge



Hip



Half round non-interlocking ridge



Clips



*Clipped Monopole tiles must also be nailed

DRY FIX AND VENTILATION

Faster, cleaner, more effective solutions for all roofs



Plastic tile ventilators

Tile ventilator
(in line) 10,000mm²
All colour-matched to tiles



Dry fix system for interlocking ridges and hips

Components:
Ventilated ridge/hip roll
(6m x 300mm)
Batten fixing straps
100mm stainless steel screws



Dry fix system for non-interlocking ridges and hips

Components:
Ventilated ridge/hip roll
(6m x 300mm)
Universal sealing joint with clamping plates
Batten fixing straps
100mm stainless steel screws

Note: Edilians does not currently supply dry fix or ventilation systems. However, suitable products, as shown above, are available from Edilians stockists.

