

Slate Specification Sheet

CS110 BEST is a blue-black slate with a smooth surface. Hand-split to a thickness of 5mm, this slate is noted for its consistency of thickness and surface appearance. Qualities that have made it a popular choice for both domestic, large commercial and conservation projects.

ORIGIN:
Quarry A Baña, León, Spain

PRODUCTION:
15.000 Tons / year.

FORMATS:
Rectangular

SIZE: (cm)
Between 30x22 to 60x30, according to formats.

UK: 40x25 & 50x25 slate and a half also available.



Note: If you are interested in other formats, please contact us.

WATER ABSORPTION	0,25%
SPECIFIC WEIGHT	2,8 (GR/CM3)
LONGITUDINAL RESISTANCE	66 MPA
CARBON CONTENT	1,5%
THICKNESS	5,0mm

Grading

All natural slate should be graded into at least 3 thicknesses prior to being loaded on to the roof. To minimize the effect of any variation in shade, slates should be selected from at least 2 crates at a time. As with any natural product, slate is subject to variance and any slates that are identified at the time of grading as potentially problematic should be cut and used as either undereaves or at the ridge.

For further information on fixing specification please contact us:

TECHNICAL SPECIFICATIONS:
CS110 BEST slates comply with all requirements of the British Standard: BS 12326

