

Declaration of Performance

1. Unique identification code of the product-type:	CS26
2. Type, batch or serial number or any other element allowing identification of construction product as required under Article 11(4):	500×250 mm, Quarry Quiroga, Lugo, Spain
3. Intended use or uses of the construction product in accordance with the applicable harmonized Technical Specification, as foreseen by the manufacturer:	Slate and carbonate slate for discontinuous roofing and cladding
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	GALIC PIZARRAS, S.L. C/ Barco de Avila 4 Bajo, O Barco de Valdeorras, Spain
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	N/A
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	AVCP System 4

7. Declared Performance

Dimensional Tolerances	
Individual thickness and variation to nominal:	4.5 mm ±35%
Deviation from declared length and width:	Complies
Deviation from edge straightness:	Complies
Deviation from squareness:	Complies
Strength (Characteristic Modulus of rupture):	Transverse: 49.6 N/mm ² Longitudinal: 57.5 N/mm ²
Performance	
Water absorption:	0.33% W _I
Freeze-thaw cycling:	Not required
Thermal cycling:	T _I
Sulfur dioxide exposure:	S _I
Non-carbonate carbon content:	0.3%. Complies (≤2%)
Carbonate content:	0.2%. Complies
Release of dangerous substances:	None in conditions of use as roofing or external cladding
External fire performance:	Deemed to satisfy
Reaction to fire:	Deemed to satisfy A ₁

8. Performance of the product identified in Points 1 and 2 is in conformity with the declared performance in Point 7.

9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.